

**TESORO
LOGISTICS NORTHWEST
PIPELINE LLC**

SLC CORE PIPELINE

LOCAL TARIFF

Applying on

CRUDE PETROLEUM

Governed, except as otherwise provided herein, by rules and regulations shown in Tesoro Logistics Northwest Pipeline LLC's F.E.R.C. No. 6.3.0, or successive issues thereof.

Filed in Compliance with 18 C.F.R. § [W] ~~344.3~~ 342.3.

ISSUED MAY 22, 2020

EFFECTIVE JULY 1, 2020

The provisions published herein will, if effective, not result in an effect on the quality of the human environment.

ISSUED BY:
S. M. LYON, Vice President
Tesoro Logistics Northwest Pipeline LLC
539 South Main Street
Findlay, Ohio 45840

COMPILED BY:
A. J. HELDMAN
Tesoro Logistics Northwest Pipeline LLC
539 South Main Street
Findlay, Ohio 45840
(419) 421-4048
ajheldman@marathonpetroleum.com

Tariff available at <https://www.marathonpipeline.com/Shippers/> and <http://www.mplx.com/Tariffs/>

TABLE OF RATES

FROM	TO	Rates in Cents per Barrel of 42 United States Gallons
Divide Junction, Uinta County, WY Evanston Junction, Uinta County, WY	Wahsatch Station, UT	[I] 11.67

NOTE 1 – When gathering service is performed, the through rate to destination will be made by adding [I] 136.10 cents per barrel to the rate named in this column.

NOTE 2 – Carrier will assess a power and flow improver surcharge of [I] 17.78 cents per barrel applicable to all volumes delivered into Granger Station or injecting into the SLC Core Pipeline system between Granger Station and Wahsatch Station.

Movements from Divide Junction or Evanston Junction to Salt Lake City may be accomplished on this tariff to Wahsatch Station and then on SLC Pipeline LLC’s FERC No. 6.0.0, or reissues thereof, from Wahsatch Station to Salt Lake City.

EXCEPTIONS AND ADDITIONS TO TESORO LOGISTICS NORTHWEST PIPELINE LLC’s F.E.R.C. NO. 6.3.0, OR REISSUES THEREOF.

ITEM NO. 30: In addition to the provisions stated in Item No. 30, Segregation and Variations in Quality and Gravity, of Tesoro Logistics Northwest Pipeline LLC’s rules and regulations tariff, F.E.R.C. No. 6.3.0, or reissues thereof, the following will apply to movements listed herein:

Crude petroleum accepted for transportation under this tariff must meet the following specifications:

- Gravity of crude petroleum must be between 45 degrees and 58 degrees API.
- Viscosity must not exceed 5 centistokes at 60° F.
- Reid Vapor Pressure (RVP) must not exceed 9.6 psi.
- Hydrogen sulfide content must be below 10 ppm.
- Sulfur content must not exceed 0.10% by weight.
- Basic sediment and water (BS&W) content must not exceed 0.3% by volume and free water content must not exceed 0.3% by volume.
- Pour point limits must not exceed +5F.

EXPLANATION OF REFERENCE MARKS:

- [W] Change in wording
- [I] Increase